

Sticky Mats

Material Safety Data Sheet**SECTION I**

MANUFACTURER'S NAME

Americover Inc

EMERGENCY TELEPHONE NO.

(800) 747-6095

ADDRESS (Number, Street, City, State and Zip Code)

P O Box 270198 San Diego, CA 92198

PRODUCT IDENTIFICATION

Sticky Mats

USE/DESCRIPTION

Tacky plastic to remove debris from shoes

DATE OF MOST RECENT REVISION

6/1/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS

CAS NO.

ACGIH-TLV

ACGIH - STEL

%

Chemical Family: Acrylic
Copolymer/Natural Rubber Blend coated
Polyethylene Film

Kathon LX 1.5% Anti Microbial agent

No Hazardous Ingredients

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT

Solid

SPECIFIC GRAVITY (H₂O = 1)

0.92-0.98 (h20)=1

VAPOR PRESSURE (mm Hg.)

(at 77°F)

N/A

MELTING POINT

230°F

VAPOR DENSITY (AIR = 1)

N/A

EVAPORATION RATE (Butyl Acetate = 1)

N/A

SOLUBILITY IN WATER

Insoluble.

APPEARANCE AND ODOR

Blue odorless flexible film tacky on one side

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method Used)

650°F (ASTM E136)

FLAMMABLE LIMITS

Thermal

LEL

UEL

EXTINGUISHING MEDIA

Carbon dioxide, water and foam.

SPECIAL FIRE FIGHTING PROCEDURES

Extinguish ignition source first and follow char path.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None

PAGE (1)

Information given herein is offered in good faith as accurate, but without guarantee. Conditions of use and suitability of the product for particular uses are beyond our control. All risks of use of the product are therefore assumed by the user and we expressly disclaim all warranties of every kind and nature, including warranties of merchantability and fitness for a particular purpose in respect to the use or suitability of the product. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents. Appropriate warnings and safe handling procedures should be provided to handlers and users.

SECTION V - REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATIBILITY (Materials to avoid)

Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may produce carbon monoxide and irritating smoke. As with all combustion, the nitrogen in the air can form nitrogen oxides. Hazardous decomposition carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION			CONDITIONS TO AVOID
	Will not occur	X	

SECTION VI - HEALTH HAZARD DATA

HEALTH HAZARDS

CARCINOGENICITY	NTP?	IARC MONOGRAPHS?	OSHA REGULATED?

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Irritation of eyes, nose, throat and skin when inhaled during fire, smoke or smoldering.

EMERGENCY AND FIRST AID PROCEDURES

EYES:

Rinse with water for 15 minutes.

SKIN:

Soap and water.

SWALLOWED:

May cause choking-consult physician promptly

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

WASTE DISPOSAL METHOD

Incinerate or put in land fill in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Transport and store under ambient temperatures and pressures.

SECTION VIII - CONTROL MEASURES: For Use Where Significant Eye, Skin Or Inhalation Exposure Is Likely

RESPIRATORY PROTECTION (Specify Type)

Not required.

VENTILATION	LOCAL EXHAUST	SPECIAL
	Not required.	
	MECHANICAL (General)	OTHER
	Not required.	

PROTECTIVE GLOVES

Not required.

EYE PROTECTION

Not required.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

None

WORK/HYGIENIC PRACTICES

Use normal work place procedures.